

## View Range - Display Tags

	Omnio Omnio	Commit D O O O O O O O O O O O O O O O O O O	Omni-ID
Products	View 2	View 3	View 4
Typical Applications	Sortation / Postal	Work-In-Process Instructions and Control	Work-In-Process Instructions and Control
	Warehousing / Yard Management	Cycling containers and kanban	Cycling containers and kanban
	Food Supply Chain	Food Supply Chain	Food Supply Chain
	Healthcare: Equipment Tracking and labeling	Health Care: Equipment Tracking and labeling	Health Care: Equipment Tracking and labeling
Screen	Eledctrophoretic e-paper display	Eledctrophoretic e-paper display	Eledctrophoretic e-paper display
	Full Graphic, 120° viewing angle (in sunlight)	Full Graphic, 120° viewing angle (in sunlight)	Full Graphic, 120° viewing angle (in sunlight)
Diagonal screen dimension (in)	2.0	2.6	4.3
User Memory	24 image pages 128 kb user space	24 image pages 128 kb user space	24 image pages 128 kb user space
Battery: Active Passive	Sealed Battery 20,000 image writes or 5 yrs RF	Sealed Battery 20,000 image writes or 5 yrs RF	Sealed Battery 20,000 image writes or 5 yrs RF
Range Active Passive	200m 8m	200m 8m	200m 8m
Size (mm)	107 x 60 x 19.4	107 x 60 x 19.4	139 x 94.6 x 19.4
Ingress Protection	IP 68 Nema 4	IP 68 Nema 4	IP 68 Nema 4
Operating Temperature (°C)	0 to +50 °C	0 to +50°C	0 to +50°C
Order Codes +	V2	V3	V4

<sup>+</sup> Order Option Codes are listed on the datasheets.