

# Z408



large character

**BSR** IDWARE


BSR idware GmbH

Jakob-Haringer-Str.3

A-5020 Salzburg

<https://www.bsr.at>

[sales@bsr.at](mailto:sales@bsr.at)



Resistance



Flexibility



Multi-control



Full integration

## Technical Specifications



**ZANASI**  
make your mark



large character

# Z408

## Printing characteristics

### PRINTING SPECIFICATIONS

Up to ten printing lines
Print height from 5 mm to 190 mm (0,2" - 7,48")
Coding throw distance up to 35 mm (1,37")
Line speed capability: up to 180 m/min (591 ft/min)
Printing rate: up to 266 ct/sec
Available fonts: 5x4, 5x5, 6x4, 7x4, 7x5, 9x5, 9x7, 10x8, 12x10, 16x10, 24x16, 32x18, 48x30 and True Type
Up to 6800 stroke per message
Messages and logos storage: up to 8 GB with expandable Micro SD memory
Automatic date, time, off sets and expiry date multifunctions
Incrementing/decreasing alphanumeric product counters up to 9 digits
Metric repeat print - message function
Customizable message repeat with single print start
Field orientation: 0°, 90°, 180°, 270°
Tower print function (text rotation of 90°)
Fixed and variable text field types (automatic or external)

### BARCODES

2/5 Industrial, UPC-A, CODE 39, EAN 13


## Construction characteristics

### CABINET

10,1" TFT full color anti-reflection high-contrast LED touch-screen display
Stainless steel structure AISI 304
Support on rubber feet
User interface and virtual keyboards with configurable foreign languages and alphabets
Temperature: from 0°C to 50°C (32° F - 122° F)
Humidity: 0-90% (non-condensing)
Single phase, 85 - 240 Vac, 50 - 60 Hz, 400 VA
Single phase, 85 - 240 Vac, 50 - 60 Hz, 800 VA (more than 32 dots)

### EXTERNAL CONNECTIONS

Serial connection RS232
Ethernet interface for LAN 10/100 connection
USB port version 2.0
Parallel interface BCD, 6 bit
Configurable I/O ports
Sensor management for product detection
Shaft encoder input for variable speed production lines
External alarm outputs for low ink level



## Usability

### PRINTER MANAGEMENT

Real time throughput counter
Management of up to four 7 or 16 dot, or two 32 dot, or one 48 dot printheads
Exclusive user interface customizable for single operator (functionality, language and alphabets...)
Intuitive user interface with graphic icons
Innovative graphic editor with Drag & Drop
Quick creation of images, shapes and lines through touch-screen display
Multi-level access with login
Online help and user manual with contextual photos and videos
Message storage with file name
Print parameters storage in the messages
Message dimension check before print


### PRINthead

"Tilt" rotation bracket to obtain up to 5 different print heights
Print heights 7 dot head: 7, 10, 12, 16 and 20 mm
Print heights 16 dot head: 16, 30, 40, 50 and 60 mm
Print heights 32 dot head: 32, 60, 80, 100 and 120 mm
Print heights 48 dot head: 50, 90, 120, 150 and 190 mm
Stainless steel structure AISI 304
High efficiency solenoid technology
Printhead - console distance: up to 10 m (33 ft)
Stainless steel nozzle plate AISI 304
High precision nozzles made of synthetic ruby
Purge and calibration per single dot

## Consumables

### INKS

Wide range of inks to satisfy any application and surface, all compliant with RoHS: water-based, ketone-based (MEK) and alcohol-based (methanol-free) inks
Food Contact certified inks for food packaging



**ZANASI**  
make your mark

ZANASI SRL Via Marche n.10  
41049 Sassuolo (MO)  
Tel. +39 0536 99.97.11

[zanasicoding.com](http://zanasicoding.com)



BSR idware GmbH

Jakob-Haringer-Str.3  
A-5020 Salzburg  
<https://www.bsr.at>  
[sales@bsr.at](mailto:sales@bsr.at)