

VOYAGER XP 1400G

Accessories Guide



BSR idware GmbH
Jakob-Haringer-Str.3
A-5020 Salzburg
<https://www.bsr.at>
sales@bsr.at

Honeywell

MOUNTING HARDWARE AND STANDS



STND-19R02-002-4

Stand: gray, 19cm (7.5') stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



STND-23F03-002-4

Stand: gray, 23cm (9') stand height, flexible rod, weighted mid-sized universal base, Voyager 1200 and 1400 cup



HOLDER-004-U

Holder: desktop/wall mount, for Voyager 1200g and Voyager 1400g



STND-19R02-002-2

Stand: black, 19cm (7.5') stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



STND-19R02-002-0

Stand: light-gray, 19cm (7.5') stand height, rigid Voyager-like plastic pole, weighted tripod base, Voyager 1200 and 1400 cup



HOLDER-005-W

Holder: wall mount hook, for Voyager 1200g and Voyager 1400g

POWER SUPPLIERS



46-00525-6

Power Supply – NA Plug

Power Supply: NA plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, LV6, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00526

Power Supply – EU Plug

Power Supply: EU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00528

Power Supply – AU Plug

Power Supply: AU plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

46-00529

Power Supply – CN Plug

Power Supply: CN plug, 1.0A @ 5.2V DC, 90-255V AC @ 50-60Hz, for use with Xenon and Voyager bases, or can be used to supply power to non-powered scanner serial cable connections.

CABLES

CBL-500-150-S00

USB Cable

Cable: USB Type A, Host 5V Power Only, 150cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-150-S00-05

USB Cable

Cable: USB Type A, Host 5V Power Only, 150cm length, Straight, No EAS, white, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-S00

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-S00-05

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Straight, No EAS, white, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-300-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-500-400-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 400cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Product

CBL-500-500-C00

USB Cable

Cable: USB Type A, Host 5V Power Only, 500cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-800-300-S00

USB Cable

Cable: USB Type C, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-800-300-C00

USB Cable

Cable: USB Type C, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-503-300-C00

USB Cable

Cable: USB 12V Locking, Host 5V Power Only, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Product

CBL-503-300-S00

USB Cable

Cable: USB 12V Locking, Host 5V Power Only, 300cm length, Straight, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-020-300-C00

RS-232 Cable

Cable: RS232 (+5V signals) DB9 Female, Host 5V Power With Option For External 5V Power, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-120-300-C00

RS-232 Cable

Cable: RS232 (+/-12V signals) DB9 Female, Host 5V Power With Option For External 5V Power, 300cm length, Coiled, No EAS, black, without ferrite, General, Compatible with RJ45 5V Scanner Products

CBL-720-300-C00

KBW Cable

Cable: KBW, black, PS2, 3m(9.8'), coiled, 5V external power with options for host power, w/o ferrite

CBL-MAG-300-S00

RS-232 Cable

Cable: RS232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3m (9.8'), straight, external power with option for host scanner power

For more information

automation.honeywell.com

Honeywell Industrial Automation

855 South Mint Street

Charlotte, NC 28202

800-582-4263

www.honeywell.com

Voyager XP 1400G Accessories Guide | Rev A | 08/25
© 2025 Honeywell International Inc.



BSR idware GmbH

Jakob-Haringer-Str.3

A-5020 Salzburg

<https://www.bsr.at>

sales@bsr.at

Honeywell